

1 pair / paire

●PIECES INCLUDED
●PIEZAS INCLUIDAS
●КОМПЛЕКТАЦИЯ

①		× 2
②		× 2
③		× 2
④		× 2
⑤		× 6
⑥		× 2
⑦		× 2

● **SPECIFICATIONS**

Size	φ 20 mm (3/4" dia.)
Continuous power handling (RMS)	100 W
Maximum music power	450 W (equivalent to 4 ohms)
Sensitivity	88 db (1 W/1 m) (equivalent to 4 ohms)
Frequency response	94 dB (1 W/0.5 m) 1 400 Hz to 69 000 Hz (−20 dB)
Crossover frequency	3 800 Hz
Cutout diameter	φ 38 mm (1-1/2" dia.)

● ESPECIFICACIONES	
Especificaciones del altavoz	
Tamaño	φ 20 mm
Cación continua de la potencia (RMS)	100 W
Máxima potencia de música	450 W (equivalente a 4 ohmios)
Sensibilidad	88 dB (1 W/1 m) 94 dB (1 W/0,5 m)
Respuesta de frecuencia	1 400 Hz a 69 000 Hz (±20 dB)
Impedancia nominal	6 Ω
Frecuencia de corte	3 800 Hz
Diámetro de Corte	φ 38 mm

Pioneer

61

Образательно прочитайте это руководство перед подключением динамика.

TS-

[illegible]

PRECAUCIÓN

1. No utilice el altavoz independientemente. Con el fin de evitar daño, asegúrese de utilizar la red especificada.
2. Asegurarse de que las terminales del altavoz y el hilo conductor no estén en contacto con el metal.
3. Para hacer la conexión consultar también el manual de instrucciones que se provee para el "reproductor".

1. Не используйте динамиче-
ские схемы. Во избежание
потомки используйте только
указанную схему.
2. Убедитесь, что проводка и
непрямые контакты динамика
не соприкасаются с металлом.
3. При подключении также к
руководству по эксплуатации
стереосистемы.

[illegible][illegible]

1. Не используйте динамики вне схемы. Во избежание помехи используйте только усилительную схему.
2. Обратите внимание, что проводка и электроконтакты динамика не сопрягаются с антенной.
3. При подключении обращайтесь также к руководству по эксплуатации автомобильного стереосистемы.

1. Не используйте динамики вне схемы. Во избежание поломки используйте только указанную схему.
2. Убедитесь, что проводка и электромонтажные контакты динамика не соприкасаются с металлом.
3. При подгонянии или минимизации расстояния к руководству по эксплуатации автомобильной стереосистемы.

Technical drawing of the 1000 Series Cable showing dimensions in inches (") and millimeters (mm). The drawing includes a side view of the cable head, a cross-section of the cable head, a cross-section of the cable body, and a cross-section of the cable body with a central conductor. Dimensions are provided for the cable head, cable body, and cable length.

Dimensions (inches / millimeters):

- Cable head length: 46 (11-3/4)
- Cable head width: 38 (11-1/2)
- Cable head diameter: $\phi 50 (1-1/2 \text{ Dia.})$
- Cable head thickness: 14 (1/2)
- Cable head internal diameter: $\phi 42 (1-5/8 \text{ Dia.})$
- Cable head internal diameter: $\phi 50 (2 \text{ Dia.})$
- Cable body length: 17 (5/8)
- Cable body diameter: $\phi 38 (1-1/2 \text{ Dia.})$
- Cable body internal diameter: $\phi 50 (2 \text{ Dia.})$
- Cable body length: 450 (17-3/4)
- Cable body diameter: $\phi 38 (1-1/2 \text{ Dia.})$
- Cable body internal diameter: $\phi 50 (2 \text{ Dia.})$
- Cable body length: 1100 (43-1/4)
- Cable body diameter: $\phi 38 (1-1/2 \text{ Dia.})$
- Cable body internal diameter: $\phi 50 (2 \text{ Dia.})$

● **Installation Fitting Guide**
To find more information for various vehicles and adaptor compatibility

● **Guide d'installation**
Pour plus d'informations sur la compatibilité des différents véhicules et adaptateurs

<http://www.pioneer-carglobal.com/speakerfitting4>

**DOME TWEETER / HP D'AIGU À DÔME
TWEETER DE CÚPULA
КУПОЛЬНЫЙ ТВИТЕР**

A
series / séries

DOMETWEETER / HP D'AIGU À DÔME

Technical drawings of the 1000 Series 1/2" components, showing three views: side, front, and top. The side view shows a tapered profile with dimensions: 46 (1-3/4) for the top width, 38 (1-1/2) for the bottom width, and a height of 14 (1/2). The front view shows a circular face with a central hole of diameter 11 (1/2) and an outer diameter of 42 (1-5/8 Dia.). The top view shows a circular face with a central hole of diameter 17 (5/8) and an outer diameter of 50 (2 Dia.).

Technical drawings of the 1000 Series 1/2" components, showing three views: side, front, and top. The side view shows a tapered profile with dimensions: 46 (1-3/4) for the top width, 38 (1-1/2) for the bottom width, and a height of 14 (1/2). The front view shows a circular face with a central hole of diameter 11 (1/2) and an outer diameter of 42 (1-5/8 Dia.). The top view shows a circular face with a central hole of diameter 17 (5/8) and an outer diameter of 50 (2 Dia.).

Technical drawings of the 1000 Series 1/2" components, showing three views: side, front, and top. The side view shows a tapered profile with dimensions: 46 (1-3/4) for the top width, 38 (1-1/2) for the bottom width, and a height of 14 (1/2). The front view shows a circular face with a central hole of diameter 11 (1/2) and an outer diameter of 42 (1-5/8 Dia.). The top view shows a circular face with a central hole of diameter 17 (5/8) and an outer diameter of 50 (2 Dia.).

Technical drawings of the 1000 Series 1/2" components, showing three views: side, front, and top. The side view shows a tapered profile with dimensions: 46 (1-3/4) for the top width, 38 (1-1/2) for the bottom width, and a height of 14 (1/2). The front view shows a circular face with a central hole of diameter 11 (1/2) and an outer diameter of 42 (1-5/8 Dia.). The top view shows a circular face with a central hole of diameter 17 (5/8) and an outer diameter of 50 (2 Dia.).

1. Polyimide(PI) tweeter diaphragm provides natural and clear vocal
2. Specially designed tweeter flange with integrated wave guide provides excellent off-axis dispersion and extended high frequency response
3. High energy neodymium magnet increases sensitivity while maintaining signal accuracy
4. Inline high-pass crossover network ensures smooth frequency response and easy installation
5. Included multi-fit adaptors for surface mounting, flush mounting and mounting in original equipment (OE) tweeter locations

1. Le diaphragme Plyimide (PI) du tweeter fournit une voix naturelle et claire
2. Bride de tweeter spécialement conçue avec guide d'onde intégré pour une excellente dispersion hors axe et une réponse haute fréquence étendue
3. Un aimant en néodyme haute énergie qui augmente la sensibilité tout en maintenant la précision du signal
4. Le passe-haut garantit une réponse en fréquence régulière et une installation facile
5. Adaptateurs multi-usage inclus pour montage en surface, montage encastré et montage dans les emplacements de tweeter d'équipement d'origine

TS-A300TW

